



LEADER THINNER L 6000 - L 6010 - L 6020

Description:

Leader thinners: thinners that provide a wide range of applications with 2 k paints, clear coat and base coat system

Product & Additives:

Leader L6000 (Fast Thinner)

For spot and panel repairs. It can also be used for complete respraying of passenger cars provided that the temperature in the spray booth does not exceed 20°C during application

Leader L6010 (Slow Thinner)

For treatment of large vehicles within the temperature range of 20 °C -25 °C

Leader L6020 (Extra Slow Thinner)

For treatment of large vehicles within the temperature range of 35 °C -25 °C

Leader thinner L6030(Metallic Thinner)

For repair or total spraying of cars with Leader base coat

Usage

Leader Clear Coat L 8000

Leader 2 K Filler L 200

Leader 2K paints

Leader base coat

Basic Raw Materials:

Various solvents

Technical Information:

Color:

Clear

Specific Gravity:

0.9±0.1 g/cm³

Mixing Ratio:

By volume

Adhere to the mixing ratios specified in the technical data sheets of the above products

Shelf Life:

4 Years if stored in original package at 25 °C

Packaging:

1 L and 5L

Precautions:

Do not handle until the material safety data sheets have been read and understood. Regulations require that all employees should be trained on material safety data sheets for chemicals used by them. The manufacturer recommends the use of an air-supplied respirator when exposed to vapors or spray mist.



LEADER THINNER L 6000 - L 6010 - L 6020